

**10% MANGANESE OCTOATE****TECHNICAL DATA SHEET**

**DESCRIPTION:** Manganese driers are intermediate in activity since they have both oxidity and polymerizing properties. Generally used in combination with Lead and Cobalt, it helps in producing hard, tough and durable films. Because of its dark color generally manganese driers is not used in white or light finished. It is produced in different metal concentrations such as 10% and 6%

**APPLICATIONS:**

1. Drier for solvent based coatings
2. Driers for printing inks

**SPECIFICATIONS:** 10 % Manganese Octoate

SR.NO	PARAMETER	STANDARD RANGE
1	Color	Reddish Brown
2	Physical Status	Liquid
3	Metal Content %	10 % $\pm$ 0.2%
4	Viscosity @ 30° C. By B4 cup	42 to 46 sec.
5	Non Volatile At 120°C/1Hr	65 $\pm$ 5%
6	Specific gravity	0.9891 $\pm$ 0.03

**PACKAGING:** 25 kgs PE Pail and 180 kgs Steel Barrel



Plot No. K-216, MIDC Waluj, Aurangabad - 431136. (Maharashtra) INDIA  
Tel / Fax : +91-0240-2554727, Tel. : +91 - 7030416426  
Email : sales@bhagwatiallied.com | bhagwatiallied@gmail.com  
Website : www.bhagwatiallied.com

**HANDLING & STORAGE:** Recommended storage temperature is between +5<sup>0</sup>C and +40<sup>0</sup> C. Keep pails tightly closed. Store and handle in a dry, well ventilated place. Keep away from sources of heat, ignition and direct sunlight in original packaging. Provide grounding and venting in order to prevent static electricity build up. Avoid any contact with organic peroxides.

**Shelf Life:** 1 Year for unopened packages at recommended storage conditions.

.....

Bhagwati Allied Products, Address: K-216, M I D C, Waluj, M I D C, MIDC, Aurangabad,  
Maharashtra 431136, Phone: 0240 255 4727