

6 % MANGANESE OCTOATE**TECHNICAL DATA SHEET**

DESCRIPTION: Manganese driers are intermediate in activity since they have both oxidizing and polymerizing properties. Generally used in combination with Lead and Cobalt, it helps in producing hard, tough and durable films. Because of its dark color generally manganese driers is not used in white or light finished. It is produced in different metal concentrations such as 10% and 6%

APPLICATIONS:

1. Drier for solvent based coatings
2. Driers for printing inks

SPECIFICATIONS: 6 % Manganese Octoate

SR.NO	PARAMETER	STANDARD RANGE
1	Metal Content %	5.8 % to 6.2%
2	Color	Reddish Brown
3	Physical status	Liquid
4	Viscosity @ 30° C. By B4 cup	12 to 16 sec.
5	Non Volatile At 120°C/1Hr	38 ± 5%
6	Specific gravity	0.8912 ± 0.03



Plot No. K-216, MIDC Waluj, Aurangabad - 431136. (Maharashtra) INDIA
Tel / Fax : +91-0240-2554727, Tel. : +91 - 7030416426
Email : rupesh@bhagwatiallied.com | bhagwatiallied@gmail.com
Website : www.bhagwatiallied.com

PACKAGING: 25 kgs PE Pail and 180 kgs Steel Barrel

HANDLING & STORAGE: Recommended storage temperature is between +5⁰C and +40⁰ C. keep pails tightly closed. Store and handle in a dry, well ventilated place. Keep away from sources of heat, ignition and direct sunlight in original packaging. Provide grounding and venting in order to prevent static electricity build up. Avoid any contact with organic peroxides.

Shelf Life: 1 Year for unopened packages at recommended storage conditions.

.....

**Bhagwati Allied Products, Address: K-216, M I D C, Waluj, M I D C, MIDC, Aurangabad,
Maharashtra 431136, Phone: 0240 255 4727**