

**15% POTASSIUM OCTOATE****TECHNICAL DATA SHEET**

**DESCRIPTION:** Potassium Octoate when combined with cobalt support the accelerating effect in unsaturated polyesters. This results in a decrease of discoloration of UPS-Systems caused by Cobalt. Further it is also capable of stabilizing the rheological and the pot life behavior of waterborne 2- components PUR systems and additionally it can positively affect the haze-values of these paint systems.

**APPLICATIONS:**

It is used in unsaturated polyesters such as in solvent-containing and waterborne systems.

**SPECIFICATIONS:** Potassium Octoate 15 %

Sr.No	PARAMETERS	STANDARD RANGE
1	Appearance	Pale yellow, brownish liquid
2	Clarity	Clear.
3	Non Volatile At 120°C/1Hr	80 ± 5 %
4	Metal Content %	15 ± 0.2 %
5	Specific gravity	1.01 ± 0.03
6	Water content (by KF)	Less than 5 %



Plot No. K-216, MIDC Waluj, Aurangabad - 431136. (Maharashtra) INDIA  
Tel / Fax : +91-0240-2554727, Tel. : +91 - 7030416426  
Email : sales@bhagwatiallied.com | bhagwatiallied@gmail.com  
Website : www.bhagwatiallied.com

**PACKAGING:** 250 kgs MS Barrel.

**HANDLING & STORAGE:** Protect from the effects of weathering and store at temperatures between 5 and 30 °C. Once opened, containers should be resealed immediately after each removal of the product. With prolonged storage of opened containers it is advisable to scavenge the vapor space above the product with nitrogen before resealing the containers

**SHELF LIFE:** 1 Year at recommended storage conditions.

---

Bhagwati Allied Products, Address: K-216, MIDC, Waluj, MIDC, MIDC, Aurangabad,  
Maharashtra 431136 Phone: 0240 255 4727