

## 6 % ZINC OCTOATE

### TECHNICAL DATA SHEET

**DESCRIPTION:** Zinc is an “auxiliary drier”, used in conjunction with the active metals. It primarily helps in keeping the film “Open” thus permitting hardening throughout. Zinc is also powerful wetting and dispersing agent and when added early in the formulation, it greatly reduces the mixing and grinding time. It is produced in different metal concentration such as 20% and 18%.

**APPLICATIONS:**

1. Driers for solvent based coatings
2. Driers for printing inks

**SPECIFICATIONS:** Zinc Octoate 6%

Sr No	PARAMETERS	STANDARD RANGE
1	Colour	Trace Yellow
2	Metal Content %	6.0% ± 0.2%
3	Specific gravity @ 30° C	0.84 ± 0.03
4	Non Volatile At 102°C/1Hr	24 % ± 5%



Plot No. K-216, MIDC Waluj, Aurangabad - 431136. (Maharashtra) INDIA  
Tel / Fax : +91-0240-2554727, Tel. : +91 - 7030416426  
Email : sales@bhagwatiallied.com | bhagwatiallied@gmail.com  
Website : [www.bhagwatiallied.com](http://www.bhagwatiallied.com)

**PACKAGING:** 25 kgs PE Pail and 180 kgs Steel Barrel.

**HANDLING & STORAGE:** Recommended storage temperature is between +5 C and +40 C. Keep pails tightly closed. Store and handle in a dry, well - ventilated place. Keep away from sources of heat, ignition and direct sunlight in original packaging. Provide grounding and venting in order to prevent static electricity build-up. Avoid any contact with Organic Peroxides.

**SHELF LIFE:** 1 Year For unopened packages at recommended storage conditions.

---

**Bhagwati Allied Products, Address: K-216, M I D C, Waluj, M I D C, MIDC, Aurangabad,  
Maharashtra 431136 Phone: 0240 255 4727**